A SOCIAL TION OF THE STATE OF T	© Co	terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri	kburn, Illinois	. All rights reserv	tion with lower	level p	arts, the	declaratio	n encomp	asses all		aterials fo	r which th	e item is an assembly ne manufacturer has leclaration.
1/32-2 1.1	_	Web Site for Informat		Form Type * Declaration Class * Distribute Class 6 - RoHS Yes/No, Homo						geneous Materials and Mfg Informat				
Supplier Information														
Company Name *		Company Unique ID		Unique ID Au	ıthority	Respo	nse Date	<b>*</b>	R	esponse D	ocument ID			
SEMTECH CORPORATIO	N	00-847-9941		DUNS		2022-	10-12							
Contact Name *	Title - Contact		Phone - Con	tact *	Email - Contact *				D 1:	. 0 .				
Adalmira (Mira) Duong	Customer/Document	Control S	805-498-211	aduong@semtech.com			ı	Duplic	ate Contac	t -> Auth	orized Re	epresentative		
Authorized Representati	Title - Representative	Э	resentative *	Email - Representativ			* S	upplier Co	mments or U	RL for Ac	lditional Ir	nformation		
Adalmira (Mira) Duong	Customer/Document	t Control S	805-498-211	2111		aduong@semtech.com								
Requester Item Number		Mfr Item Number		Mfr Item Name	Effectiv	e Date	Version Ma		uring Site	Weight	* U	ОМ	Unit Type	
		Rclamp3324P.TNT		Low Capacita	4 China			China		3.46877	797 m	g	Each	
Alternate Recommenda	ation							Alternate	Item Con	ments	•			
Manufacturing Proces	s In	formation												
Terminal Plating / Grid Array I	Materi	ial	Terminal B	ase Alloy	J-STD-020 MSL Ra	ating	Peak Proc	ess Body	Temperat	ure Max Ti	me at Peak Te	emperature	Number	of Reflow Cycles
Nickel/Palladium/Gold (Ni/Pd/Au) CU Alloy			,	260			<b>260</b> C		30 seconds 3					
Comments			!		1								!	
Rclamp3324P.TNT is REA	ACH-	- compliant product	, per EU R	egulation EC	1907/2006 to inc	lude th	e most re	ecent ad	ditions t	o the SVH	C candidate	list of s	ubstance	s. chk. AD

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type \*** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance \* Accepted **RoHS Declaration \*** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature** 

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

## **Homogeneous Material Composition Declaration for Electronic Products**

**Subltem Instructions:** The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

**Substance Instructions:** [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem						Homogeneous	Mojaht	Unit of			Laval	Substance Cotegory			Cubatanaa	CAS	Evennt	Weight	Unit of	Tolerance		DDM
	Name			Material	Weight	Measure			Level	Substance Category			Substance	CAS	Exempt	weight	Measure	-	+	PPM			
+1 -1	Die	+M	-M	Doped Silicon	0.02796	mg	+C	-C	Supplier		+S	-S	Si	7440-21-3		0.02796	mg			8,060.4			
+1 -1	LeadFrame	+M	-M	SGP2510P8 Sub	1.44330	<b>7</b> mg	+C	-C	Supplier		+S	-S	Copper	7440-50-8		0.632890	mg			82,453			
	-										+S	-S	Thermosetting resin	Proprietary		0.129897	mg			37,447			
											+S	-S	Glass cloth	65997-17-3		0.144330	mg			41,608			
											+S	-S	Copper foil	7440-50-8		0.288661	mg			83,216			
											+S	-S	Bariom sulfate	7727-43-7		0.036082	mg			10,402			
											+S	-S	Talc	14807-96-6		0.002164	mg			624.12			
											+S	-S	Resin	Proprietary		0.050515	mg			14,562			
											+S	-s	Nickel(Ni)	7440-02-0		0.064948	mg			18,723			
											+S	-s	palladium(Pd)	7440-05-3		0.072165	mg			20,804			
											+S	-s	Gold(Au)	7440-57-3		0.021649	mg			6,241.2			
+1 -1	Bonding wire	+M	-M	Copper wire with	0.01220	3mg	+C	-c	Supplier		+S	-S	Cu	7440-50-8	•	0.011898	mg			3,430.1			
		•									+S	-s	Pd	7440-053		0.000305	mg			87.951			
+1 -1	Molding compound	+M	-M	EME-G760L	1.97846	9mg	+C	-c	Supplier		+S	-S	Silica (Amorphous) A	60676-86-0	•	1.533313	mg			442,03			
		•									+S	-s	Silica (Amorphous) B	7631-86-9		0.158277	mg			45,629			
											+S	-s	Epoxy resin	Proprietary		0.158277	mg			45,629			
											+S	-s	Phenol resin	Proprietary		0.059354	mg			17,110			
											+S	-s	Metal Hydroxide	Proprietary		0.059354	mg			17,110			
											+S	-s	Carbon Black	1333-86-4		0.009892	mg			2,851.8			
+1 -1	Die attached Epoxy	+M	-M	8006NS	0.00684	mg	+C	-c	Supplier		+S	-S	Aluminum oxide	1344-28-1	•	0.002667	mg			769.03			
											+S	-s	Diethylene glycol mono	112-15-2		0.00171	mg			492.96			
											+S	-S	Epoxy resins	Proprietary		0.000684	mg			197.18			
											+S	-s	Epoxy resins	Proprietary		0.000684	mg			197.18			

+C -C Supplier	+S	-s	Epoxy resins	Proprietary	0.000649	mg	187.32
+C -C Supplier	+S	-S	Dapsone	80-08-0	0.000205	mg	59.156
+C -C Supplier	+S	-S	Amorphous fumed silic	68611-44-9	0.000205	mg	187.32
+C -C Supplier	+S	-S	Substituted silane	Proprietary	0.000034	mg	9.8593